



**A powerful, environmentally friendly, non-toxic biological oil cleaner and degreaser.**

OT8 rapidly removes and digests oil contamination from porous surfaces such as blockwork, paving stones, concrete, driveways, garage floors and forecourts.

Our combination of eco-friendly formulation and high performance cleaning makes OT8 the perfect all-purpose oil stain removal solution - **OT8 gives you industrial strength results without the hazards of others products!**



## Why choose OT8?

**One of the most effective products on the market:** product satisfaction guaranteed

**Quick and easy:** supplied ready to use and works in minutes!

**Biological action:** naturally digests and permanently removes oil contamination

**Non-toxic, non-flammable and low hazard:** safe for the user and the environment

**Versatile:** suitable for use on a wide variety of surfaces, indoors and outdoors

**Trusted:** used by many companies and satisfied customers for over twenty years

**Environmentally friendly:** VOC free, biological and biodegradable

**New formulation!** Reformulated for improved effectiveness and reduced hazard profile



## How it works

**OT8's unique formula works in two ways:**

- A blend of effective solvents and surfactants penetrates and lifts oil from the surface
- Specially selected bacteria naturally digest the oil - converting hydrocarbon contamination into carbon dioxide and water - to completely remove the stain

## Physical properties

Appearance	Cream to light tan viscous liquid
Bacterial count	2.0 x 10 <sup>7</sup> cfu/ml
Specific Gravity	1.07
pH @ 20°C	approx. 4
Biodegradability	>56% BOD/COD (20 days)
Shelf life	Two years after manufacture

## How to use

- Shake container well.
- Water wet the oil stain before applying OT8.
- Brush into the stain using a soft brush until OT8 changes colour from off-white to brown.
- Leave for 20 minutes and water rinse.
- Approximately 1 litre of OT8 treats 1 square metre.

**Note:** On old, weathered and ingrained oil stains, the oil stain may "re-appear". This is because the bacteria in OT8 keep working after application to bring the ingrained oil to the surface: it may be necessary for OT8 to be applied more than once.

OT8 is not suitable for use on tarmac or asphalt surfaces and is not designed for use on removing stains of for use on hydraulic fluid, wood, synthetic or mineral oils. Further application advice can be found on our website.

## Pack sizes

12 x 1 Litre	OT8-12X1	4 x 5 Litre	OT8-4X5
25 Litre	OT8-25	200 Litre	OT8-200
1000 Litre	OT8-1000		



**"I have just used your OT8 oil cleaning kit on my old oil stain in my drive. There is only two words for it - ABSOLUTELY AMAZING!!"**

Barrie Knapp, UK



### Oil Technics Ltd

Linton Business Park, Gourdon, Aberdeenshire, Scotland UK DD10 0NH

**T:** +44 (0) 1561 361515 **E:** info@oiltechnics.com **W:** www.oiltechnics.com

Oil Technics Ltd reserve the right to modify any specification at any time and without prior notice.



FM 696382 EMS 696323