

HFD

Precision Cleaning Solvent



A residue free, high dielectric strength (50,000V), fast drying solvent degreaser.

KEY PROPERTIES

- Dries quickly and Residue free
- Effective in cleaning a wide range of oils, greases and fluxes.
- Safe for use on electric motors, windings, circuit boards and precision engineering components.
- High dielectric strength – 50,000V
- Harmless on plastics, rubbers, elastomers and painted surfaces (may swell some soft seals)

APPLICATION

- Excellent for cleaning precision metal or plastic components and electrical components.
- Can be used as supplied in dip tanks, spray machines and ultrasonic baths.
- Available in trigger spray for bench top use.
- Not recommended for use on live equipment.
- For advice on application, please contact Oil Technics on +44 (0) 1561 361515.

TECHNICAL DATA

Appearance	Clear colourless liquid	SG	0.76
Flash Point	> 62°C (closed cup)	VOC Content	100%

PACKAGING

1000L, 200L, 25L, 4 x 5L, 12 x 0.5L Trigger Sprays

SAFE HANDLING AND STORAGE

Store in original containers off the ground and out of direct sunlight. Avoid extremes of temperature.

Shelf life: 4 years from Date of Manufacture.

For guidance on handling and disposal see Material Safety Data Sheet.



Manufactured and supplied by

Oil Technics Ltd.

Linton Business Park, Gourdon,
Aberdeenshire, Scotland UK DD10 0NH

Tel: +44 (0) 1561 361515

Email: info@oiltechnics.com

Fax:

Web:



ISO 9001
FM 26186

ISO 14001
EMS 575801

+44 (0) 561 361001

www.oiltechnics.com