



MATERIAL SAFETY DATA SHEET

A. Identification of the Substance / Preparation and of the Company Undertaking

Product Name:	SpECbuild EM base		
Product Use:	Concrete Repair		
Company:	Speciality Engineering Chemicals FZE		
Address:	P. O. Box 61347, Dubai, U.A.E.		
Telephone:	+971-4-8836662	Facsimile:	+971-4-8837696
E-mail:	info@spec.ae	Web site:	www.spec.ws

B. Composition / Information on Ingredients

Composition:	Blend of epoxy resin and inorganic fillers.				
Hazardous Ingredient(s)		Symbol	CAS No.	Risk Phrases	%
Bisphenol A epoxy resin		Xi, N	25068-38-6	R36/R38/R43	80-90
Glycidyl ether of (C12-C14 alcohols	Xi, N	68609-97-2	R36/R38/R43/R51	3-20

C. Hazards Identification

Environmentally hazardous. Irritating to eyes and skin. May cause sensitization by skin contact





D. First Aid Measures

General:	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
Eyes:	Check for and remove contact lenses if any. irrigate copious amount of water for several minutes keeping eye lids open. Obtain medical attention if problem persists.
Skin:	Wash thoroughly with soap and water or suitable skin cleanser immediately. Obtain medical attention if problem persists.
Inhalation:	Remove to fresh air. If not breathing or irregular breathing, provide artificial respiration. Seek medical attention if the problem continues.
Ingestion:	Do not induce vomiting. Obtain medical attention and show the container or label.

E. Fire Fighting Measures

Suitable Extinguishing Media:	CO_2 / Dry chemical powder. Do not use water jets.
Special Exposure Hazards:	Toxic fumes.
Special Protective Equipment:	Self - contained breathing apparatus.

F. Accidental Release Measures

 Personal Precautions:
 Wear gloves and other protective clothing including eye/face protection.

 Issue: 02
 QA-041
 Date: 01-Jan-06
 Product Name: SpECbuild EM base
 Page: 1 of 3

Environmental Precautions:	Prevent entry into drains, sewers and water courses.
Decontamination Procedures:	Soak-up with inert absorbent or contain and remove by best available means. Gather into containers. Dispose as waste.

G. Handling and Storage				
Handling:	Avoid skin and eye contact. Do not eat, drink or smoke whilst using this product. Ensure adequate ventilation.			
Storage:	Keep containers dry, cool and tightly closed.			
Decontamination Procedure:	Soak-up with inert absorbent or contain and remove by best available means. Gather into containers. Dispose of as waste.			

H. Exposure Controls / Personal Protection

Occupational Exposure Limits:	None assigned
Engineering Control Measures:	Use with adequate general and local exhaust ventilation.
Personal Protective Equipment:	Impervious gloves, safety goggles, plastic apron.

I. Physical and Chemical Properties

State:	Liquid
Colour:	Clear
Odour:	Faint
Flash Point (°C):	>150
SG/Bulk Density:	1.15
Solubility:	Insoluble

J. Stability and Reactivity

Stability:	Stable under recommended conditions.
Conditions to avoid:	Not known.
Materials to avoid:	Strong acids, alkalies and oxidising agents.
Hazardous Decomposition products:	Carbon monoxide. Irritant fumes.

K. Toxicological Information

There are no date available on the preparation itself. This has been assessed following the conventional method of the Preparations Directive 1999/45/EC and classified for toxicological hazards accordingly.

Based on the properties of the epoxy constituent(s) and considering toxicological data on similar preparations, this product may be a skin sensitiser and irritant. May produce allergic reactions.

L. Ecological Information

When used and disposed as intended, no adverse environmental effects are foreseen. Expected to be not readily biodegradable. Bio-accumulative potential and ecotoxicity are not determined.

Issue: 02	QA-041	Date: 01-Jan-06	Product Name: SpECbuild EM base	Page: 2 of 3
-----------	--------	-----------------	---------------------------------	--------------

M. Disposal Considerations

Disposal must be in accordance with local and national legislation.

Do not allow to enter drains or watercourses. Material and container must be disposed as hazardous waste.

N. Transport Information

Proper shipping name:	Environmentally hazardous	substance, liquid, N.O.S.	
UN Number:	3082		
Class :	9		
Subsidiary risk:	-		
Packing Group:	Ш	A	
Label(s):		MARINE POLLUTANT	
Additional Information	\sim		
ADR-HIN:	90		
IMDG-EMS:	F-A, S-F	Marine Pollutant:	Yes
IMO:	T1		

O. Regulatory Information

EU Regulations:	The product is labeled as follows, in accordance with local regulations.
Hazard Symbol(s):	Xi, N
Contains:	Bisphenol-A epoxy resin
Risk Phrases:	R36 - Irritating to eyes R38 - Irritating to skin R43 - May cause sensitisation by skin contact
Safety Phrases:	S28 - After contact with skin, wash immediately with plenty of water S39 - Wear eye/face protection S61 - Avoid release to the environment. Refer to special instructions/MSDS

P. Other Information

Issue no.:	2
Issue date:	01-Jan-06
Issued by:	SpEC Technical Department

No liability accepted for any injury, loss, damage or cost arising directly or indirectly from the use of any information contained within this MSDS since the customers treatment of the product is necessarily out of our control.

The data given above is based upon current knowledge and experience. This safety sheet is intended to describe our products in terms of their safety requirements. It does not guarantee the properties of the products described.





MATERIAL SAFETY DATA SHEET

A. Identification of the Substance / Preparation and of the Company Undertaking

Product Name:	SpECbuild EM Hardener		
Product Use:	Concrete Repair		
Company:	Speciality Engineering Chemicals FZE		
Address:	P. O. Box 61347, Dubai, U.A.E.		
Telephone:	+971-4-8836662	Facsimile:	+971-4-8837696
E-mail:	info@spec.ae	Web site:	www.spec.ws

B. Composition / Information on Ingredients

Composition:	Epoxy hardener, diluents and inorganic fillers mixture.				
Hazardous Ingr	edient(s)	Symbol	CAS No.	Risk Phrases	%
Isophorone diam	ine	C, Xn	2855-13-2	R34/R36/R43	<20
Formaldehyde po	olymer solution	Xn, F	25155-81-1	R11/R20	2-4

C. Hazards Identification

Corrosive May cause burns Toxic to aquatic organisms		1 And
	CORROSIVE	Hezardous to

D. First Aid Measures

General:	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
Eyes:	Check for and remove contact lenses if any. Irrigate copious amount of water for several minutes keeping eye lids open. Obtain medical attention if problem persists.
Skin:	Wash thoroughly with soap and water or suitable skin cleanser immediately. Obtain medical attention if problem persists.
Inhalation:	Remove to fresh air. If not breathing or irregular breathing, provide artificial respiration. Seek medical attention if the problem continues.
Ingestion:	Do not induce vomiting. Obtain medical attention and show the container or label.

E. Fire Fighting Measures

Suitable Extinguishing Media:	CO_2 / Dry chemical powder. Do not use water jets.
Special Exposure Hazards:	Toxic fumes.
Special Protective Equipment:	Self - contained breathing apparatus.

F. Accidental Release Measures

Personal Pred	cautions:	: Wear gloves and other suitable protective clothing.		
Issue: 02	QA-041	Date: 01-Jan-06	Product Name: SpECbuild EM hardener	Page: 1 of 3

Environmental Precautions:Prevent entry into drains, sewers and water courses.Decontamination Procedures:Soak-up with inert absorbent or contain and remove by best available means. Gather

into containers. Dispose of as waste.

G. Handling and Storage	
Handling:	Avoid skin and eye contact. Do not eat, drink or smoke whilst using this product. Ensure adequate ventilation.
Storage:	Keep containers dry, cool and tightly closed.
Decontamination Procedure:	Soak-up with inert absorbent or contain and remove by best available means. Gather into containers. Dispose of as hazardous waste.

H. Exposure Controls / Personal Protection

Occupational Exposure Limits:None assignedEngineering Control Measures:Use with adequate general and local exhaust ventilation.Personal Protective Equipment:Impervious gloves, safety goggles, plastic apron.

I. Physical and Chemical Properties

State:	Liquid
Colour:	Amber
Odour:	Amines
Flash Point (°C):	>150
SG/Bulk Density:	1.00
Solubility:	Miscible

J. Stability and Reactivity

Stability:	Stable under recommended conditions.
Conditions to avoid:	Not known.
Materials to avoid:	Strong acids, alkalies and oxidising agents.
Hazardous Decomposition products:	Carbon monoxide. Irritant fumes.

K. Toxicological Information

There are no date available on the preparation itself. This has been assessed following the conventional method of the Preparations Directive 1999/45/EC and classified for toxicological hazards accordingly.

Based on the properties of the epoxy constituent(s) and considering toxicological data on similar preparations, this product may be a skin sensitiser and irritant. May produce allergic reactions. May cause damage to eyes.

LD50 oral, rat: 1030mg/kg

L. Ecological Information

When used and disposed as intended, no adverse environmental effects are foreseen. Expected to be not readily biodegradable. Bio-accumulative potential and ecotoxicity are not determined.

Issue: 02	QA-041	Date: 01-Jan-06	Product Name: SpECbuild EM hardener	Page: 2 of 3
-----------	--------	-----------------	-------------------------------------	--------------

M. Disposal Considerations

Disposal must be in accordance with local and national legislation.

Do not allow to enter drains or watercourses. Material and container must be disposed as hazardous waste.

N. Transport Information

Polyamines, liquid, corro	sive, N.O.S.	
	,	
2735		
8		
-		
I		
CORROSIVE	XX	
8		
80		
F-A, S-B	Marine Pollutant:	Yes
T11		
	2735 8 - I I 80 F-A, S-B	8 I I Sources Bo F-A, S-B Marine Pollutant:

O. Regulatory Information

EU Regulations:	The product is labeled as follows, in accordance with local regulations.
Hazard Symbol(s):	C, Xn
Contains:	Polyamines
Risk Phrases:	R34 - Causes burns R51 - Toxic to aquatic organisms R53 - May cause long term adverse effects in the aquatic environment
Safety Phrases:	S25 - Avoid contact with eyes S37 - Wear suitable gloves S39 - Wear eye/face protection S61 - Avoid release to the environment. Refer to special instructions/MSDS

P. Other Information

Issue no.:	2
Issue date:	01-Jan-06
Issued by:	SpEC Technical Department

No liability accepted for any injury, loss, damage or cost arising directly or indirectly from the use of any information contained within this MSDS since the customers treatment of the product is necessarily out of our control.

The data given above is based upon current knowledge and experience. This safety sheet is intended to describe our products in terms of their safety requirements. It does not guarantee the properties of the products described.

1	Issue: 02	QA-041	Date: 01-Jan-06	Product Name: SpECbuild EM hardener	Page: 3 of 3
	15500. 02	IQX-0+1		I Toduct Name. Speebuild Em hardener	





MATERIAL SAFETY DATA SHEET

A. Identification of the Substance / Preparation and of the Company Undertaking

Product Name:	SpECbuild EM Filler		
Product Use:	Concrete Repair		
Company:	Speciality Engineering Chemicals FZE		
Address:	P. O. Box 61347, Dubai, U.A.E.		
Telephone:	+971-4-8836662	Facsimile:	+971-4-8837696
E-mail:	info@spec.ae	Web site:	www.spec.ws

B. Composition / Information on Ingredients

Composition:	Graded silica sands.				
Hazardous Ingred	dient(s)	Symbol	CAS No.	Risk Phrases	%
Silica, Quartz		Xn	14808-60-7	R22	2560

C. Hazards Identification

Harmful if swallowed.



D. First Aid Measures

General:	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
Eyes:	Check for and remove contact lenses if any. irrigate copious amount of water for several minutes keeping eye lids open. Obtain medical attention if problem persists.
Skin:	Wash thoroughly with soap and water or suitable skin cleanser immediately. Obtain medical attention if problem persists.
Inhalation:	Remove to fresh air. If not breathing or irregular breathing, provide artificial respiration. Seek medical attention if the problem continues.
Ingestion:	Do not induce vomiting. Obtain medical attention and show the container or label.

E. Fire Fighting Measures

Suitable Extinguishing Media: Not flammable.

Special Exposure Hazards: None.

Special Protective Equipment: None.

F. Accidental Release Measures

Personal Precautions: Wear gloves		and other suitable protective clothing.	
Environmental Precautions: Preve		y into drains, sewers and water courses.	
Issue: 02 QA-041 Date	: 01-Jan-06	Product Name: SpECbuild EM filler	Page: 1 of 3

Decontamination Procedures:

Gather into containers. Avoid formation of dust in atmosphere. Residue may be flushed to the drains with large volume of water.

G. Handling and Storage

Handling:	Avoid creating dust. Use eye/face protection. Ensure adequate ventilation.
Storage:	Store in dry and cool area.
Decontamination Procedure:	Gather into containers. Avoid formation of dust in atmosphere.

H. Exposure Controls / Personal Protection

Occupational Exposure Limits:	None assigned		
Substance	8 Hour TWA	STEL	Source/Other Information
Silica, amorphous: total inhalable dust respirable dust	5 mgm ⁻³ 3 mgm ⁻³		ЕН 40
Engineering Control Measures:	atmospheric levels of dust must be maintained within the Occupational exposure standard. Where mechanical methods are in adequate, appropriate personal protec- tion equipment must be used.		
Personal Protective Equipment:	Impervious gloves, goggle	s, approved dust m	nask.

I. Physical and Chemical Properties

State:	Solid - Powder
Colour:	Various
Odour:	-
Flash Point (°C):	-
SG/Bulk Density:	1890 kg/m³
Solubility:	Insoluble

J. Stability and Reactivity

Stability:	Stable under recommended conditions.
Conditions to avoid:	Exposure to air. Contamination with water.
Materials to avoid:	None.
Hazardous Decomposition products:	None.

K. Toxicological Information

May cause transient irritation to eyes

May cause irritation by inhalation and if swallowed.

L. Ecological Information

When used and disposed as intended, no adverse environmental effects are foreseen. Expected to be not readily biodegradable. Bio-accumulative potential and ecotoxicity are not determined.

Issue: 02 QA-041 Date	e: 01-Jan-06 Product Name: SpECbuild EM filler	Page: 2 of 3
-----------------------	--	--------------

M. Disposal Considerations

Disposal must be in accordance with local and national legislation.

Do not allow to enter drains or watercourses. Material and container must be disposed as hazardous waste.

N.	Transport Information	
----	------------------------------	--

Proper Shipping name:	Graded silica sands		
UN Number:	Not classified as hazardou	us for transport.	
Class:	-		
Subsidiary risk:	-		
Packaging group:	-		
Label:	-		
Additional information			
ADR-HIN:	-		
IMDG-EMS:	-	Marine Pollutant:	No
IMO:			

0.	Regulatory	Information
----	------------	-------------

EU Regulations:	The product is labeled as follows, in accordance with local regulations.
Hazard Symbol(s):	Xn
Contains:	Silica, Quartz
Risk Phrases:	R22 - Harmful if swallowed R36 - Irritating to eyes
Safety Phrases:	S36 - Wear suitable protective clothing S39 - Wear eye/face protection

P. Other Information

Issue no.:	2
Issue date:	01-Jan-06
Issued by:	SpEC Technical Department

No liability accepted for any injury, loss, damage or cost arising directly or indirectly from the use of any information contained within this MSDS since the customers treatment of the product is necessarily out of our control.

The data given above is based upon current knowledge and experience. This safety sheet is intended to describe our products in terms of their safety requirements. It does not guarantee the properties of the products described.