









MATERIAL SAFETY DATA SHEET

1. Identification of the Substance / Preparation and of the Company Undertaking

Product Name: SpECgrout E60 Filler

Product Use: Grout

Company: Speciality Engineering Chemicals FZE

Address: P. O. Box 61347, Dubai, U.A.E.

Telephone: +971-4-8836662 Facsimile: +971-4-8837696

E-mail: info@spec.ae Web site: www.spec.ae

2. Composition / Information on Ingredients

Composition: Graded silica sands.

Hazardous Ingredient(s) Symbol CAS No. Risk Phrases %

Silica, Quartz Xn 14808-60-7 R22 25–60

3. Hazards Identification

Harmful if swallowed.



4. First Aid Measures

General: In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth

to an unconscious person.

Eyes: Check for and remove contact lenses if any, irrigate copious amount of water for several minutes

keeping eye lids open. Obtain medical attention if problem persists.

Skin: Wash thoroughly with soap and water or suitable skin cleanser immediately. Obtain medical attention if

problem persists.

Inhalation: Remove to fresh air. If not breathing or irregular breathing, provide artificial respiration. Seek medical

attention if the problem continues.

Ingestion: Do not induce vomiting. Obtain medical attention and show the container or label.

5. Fire Fighting Measures

Suitable Extinguishing Media: Not flammable.

Special Exposure Hazards: None.

Special Protective Equipment: None.

6. Accidental Release Measures

Personal Precautions: Wear gloves and other suitable protective clothing.

Environmental Precautions: Prevent entry into drains, sewers and water courses.

Issue: 04 | QA-041 | Date: 13-Sep-22 | Product Name: SpECgrout E60 filler | Page: 1 of 3

Decontamination Procedures: Gather into containers. Avoid formation of dust in atmosphere. Residue may be

flushed to the drains with large volume of water.

7. Handling and Storage

Handling: Avoid creating dust. Use eye/face protection. Ensure adequate ventilation.

Storage: Store in dry and cool area.

Decontamination Procedure: Gather into containers. Avoid formation of dust in atmosphere.

8. Exposure Controls / Personal Protection

Occupational Exposure Limits: None assigned

Substance 8 Hour TWA STEL Source/Other Information

Silica, amorphous:

total inhalable dust 5 mgm⁻³ — EH 40

respirable dust 3 mgm⁻³

Engineering Control Measures: atmospheric levels of dust must be maintained within the Occupational exposure

standard. Where mechanical methods are in adequate, appropriate personal protec-

tion equipment must be used.

Personal Protective Equipment: Impervious gloves, goggles, approved dust mask.

9. Physical and Chemical Properties

State: Solid - Powder

Colour: Various

Odour: -

Flash Point (°C):

SG/Bulk Density: 1890 kg/m³

Solubility: Insoluble

10. Stability and Reactivity

Stability: Stable under recommended conditions.

Conditions to avoid: Exposure to air. Contamination with water.

Materials to avoid: None.

Hazardous Decomposition products: None.

11. Toxicological Information

May cause transient irritation to eyes

May cause irritation by inhalation and if swallowed.

12. Ecological Information

When used and disposed as intended, no adverse environmental effects are foreseen. Expected to be not readily biodegradable. Bio-accumulative potential and ecotoxicity are not determined.

Issue: 04	OA-041	Date: 13-Sep-22	Product Name: SpECgrout E60 filler	Page: 2 of 3

13. Disposal Considerations

Disposal must be in accordance with local and national legislation.

Do not allow to enter drains or watercourses. Material and container must be disposed as hazardous waste.

14. Transport Information

Proper Shipping name: Graded silica sands

UN Number: Not classified as hazardous for transport

IMO Class: Not classified as hazardous for transport

IATA/ICAO Class: Not classified as hazardous for transport

ADR Class: Not classified as hazardous for transport

Subsidiary risk: -

Packaging group: -

Label: -

Additional information

ADR-HIN: -

IMDG-EMS: - Marine Pollutant: No

IMO:

15. Regulatory Information

EU Regulations: The product is labeled as follows, in accordance with local regulations.

Hazard Symbol(s): Xn

Contains: Silica, Quartz

Risk Phrases: R22 - Harmful if swallowed

R36 - Irritating to eyes

Safety Phrases: S36 - Wear suitable protective clothing

S39 - Wear eye/face protection

16. Other Information

Issue no.:

Issue date: 12-0ct-10

Issued by: SpEC Technical Department

No liability accepted for any injury, loss, damage or cost arising directly or indirectly from the use of any information contained within this MSDS since the customers treatment of the product is necessarily out of our control.

The data given above is based upon current knowledge and experience. This safety sheet is intended to describe our products in terms of their safety requirements. It does not guarantee the properties of the products described.

Issue: 04 QA-041 Date: 13-Sep-22 Product Name: SpECgrout E60 filler Page: 3 of 3